



LED CITY POLES

Ordering Information

Example: LCP-BER-AL-20-4040-188-CAG-SN-PW60-50-ST-MV-14055-PWC-BK-FBCP

Product Family	Design	Material	Height	Base OD	Top OD	Wall Thickness
LCP = LEDCITYPOLES	BER= Berlin Aluminum Anchor Base	AL = Aluminum ST = Steel SST = Stainless Steel	10-20 = 10-30' C = Custom	30 = 3" 40 = 4" 45 = 4.5" 5 = 5" C = Custom	30 = 3" 40 = 4" 45 = 4.5" 5 = 5" C = Custom	125 = 0,125" 188= 0,188" C = Custom

Anchor Bolts	Fixture Mounting	Performance (Watts = Nominal Lumens Per Fixture)	Color Temp	Voltage	Distribution	Finish Type
AB = Includes Anchor Bolts LAB = Less Anchor Bolts CAG = Includes Anchor Cage C = Custom	SN=Single (One side) DT=Double 180 (Two sides) DL=Double 90 (Two sides) TT=Triple 90x90x180 (Three sides) Q4=Quadruple (Four sides)	PW30 = 4,050 PW60 = 8,100 PW90 = 12,150 PW120 = 16,200 CW = Custom	30 = 3000K, 70 CRI 40 = 4000K, 70 CRI 50 = 5000K, 70 CRI CT = Custom	MV = 120-277V HV = 277-480V CV = Custom	14895_(15DG) 14891_(30DG) 14130_(60DG) 14263_(90DG) 12862 (Type II) 14055(Type II) 17255(Type III) CD = Custom	GAL = Galvanized Only (No Paint) PWC = Powder coated PWGV = Powder coating Over Galvanizing C = Custom

Painted Color	Option	Accessories
BK = Black (Standard) WH = White (Standard) NA = Nat Alum Silver GM = Graphite Metallic DP = Dark Platinum DB = Dark Bronze (Standard) MB = Medium Bronze (Standard) LG = Light Gray SG = Slate Gray DG = Dark Green SL = Silver RAL = Custom RAL Match C = Custom	SPL = Special Cut Length (Please Specify) BCSPCL = Special Base Plate to Match Existing Bolt Circle VDA = Internal Vibration Dampener, Factory Installed FBCP = ABS Plastic Full Base Cover FBSC = Steel Full Base Cover PXDX = Side Drill + Tenon w/ Additional Hand Hole (Specify Tenon OD & Length) EHH = Additional Hand Hole Opening w/ Cover Assembly	STAMP = Engineering Services, Signed & Sealed Calcs STAMPCA = Engineering Services, CA Signed & Sealed Calcs PRE075 = Pre-Ship Anchor Bolts - 0.75" x 17" x 3" PRE075 = Pre-Ship Anchor Cages - 0.75" x 17" x 3"